

High-Performance Dual-Channel Reference Class Electrometer*

DOSE²



Independent Dual-Channel

- > Two independent measurement channels
- ➤ Independent control of applied system factor, range and bias voltage
- Wide measurement range for advanced applications

Accuracy and Stability

- Reference Class Electrometer
- Significantly exceeds IEC 60731 and AAPM ADCL recommendations

Workflow Efficiency

- > Threshold triggered measurement mode
- Intuitive touchscreen operated interface
- Simple data export via USB

DOSE²

High-Performance Dual-Channel Reference Class Electrometer

for reference dose and dose rate measurements in radiation therapy





-0.018 na



ment readouts. Three charge collection modes support measurements in a variety of

clinical applications.

-0.045 -0.018-0.000~ 0.000

Additional features and benefits:

- Real-time display of dose & dose-rate
- ➤ Date & time stamp of all measurements for clear identification
- > Set automatic repeat measurements
- ➤ Built in chamber library for simple setup
- Integrated check source utility to ensure current strength or project future strength
- > Both channels feature extensive range (0.001 pA to 500.0 nA, 0.001 pC to 999.9 µC) for a wide application, including ratio measurements

Performance Characteristics	DOSE ²	Relevant ref. class limits as documented in IEC60731 standard
Repeatability	± 0.1 %	± 0.25 %
Long-term stability	± 0.5 % (over 1 year)	± 0.5 % (over 1 year)
Zero drift	± 0.25 %	± 0.5 %
Non-linearity	± 0.25 %	± 0.5 %
Response time	< 2 sec (high range) < 12 sec (low range)	< 3 sec
Stabilization time	± 0.1 %	± 0.5 % Min rated range = 15 min to 6 h
Dose rate dependence	< 0.5 %	± 0.5 %
Dimensions mm (LxWxH)	Housing: 286 x 210 x 76 Housing with handle: 304 x 270 x 76	
Weight	2.4 kg	

CONTACT

dosimetry-info@iba-group.com Europe, Middle East, Africa | Tel.: +49 9128 607 0 North America, Latin America | Tel.: +1 901 386 2242 Asia Pacific | Tel.: +86 10 8080 9288

www.iba-dosimetry.com

